

# SWAGING EQUIPMENT

## UNIFLEX HM200 / HM200 ECOLINE

Compact , strong,  
universal



|  | HM 200          | HM 200 ecoline                       |
|--|-----------------|--------------------------------------|
| Presskraft (kN/Ton) / Crimp force  | 1300 / 130      | 1300 / 130                           |
| Schmierung entfällt: 20% weniger Reibung<br>No grease: 20% less friction | ✓               | ✓                                    |
| Steuerung / Control  | Control A       | ecoline                              |
| SAE R 13* 1 Teil Armatur / 1 piece                                       | 1 1/2"          | 1 1/2"                               |
| SAE R 12* 2 Teil Armatur / 1 piece                                       | 1 1/2"          | 1 1/4"                               |
| SAE R 13* 2 Teil Armatur / 2 piece                                       | 1"              | 1"                                   |
| SAE R 12* 2 Teil Armatur / 2 piece                                       | 1 1/4"          | 1"                                   |
| Industrie / Industrial   | 2"              | 2"                                   |
| 90° Bogen / Elbows   | 1 1/2"          | 1 1/2"                               |
| Max. Pressbereich / Crimp range  | 70 mm           | 70 mm                                |
| Öffnungsweg / Opening  | + 30 mm         | + 30 mm                              |
| Öffnung ohne Backen /<br>Opening without dies                            | 100 mm          | 100 mm                               |
| Backentyp / Type of dies   | 239             | 239                                  |
| Geschwindigkeit (mm/sec.) / Speed  |                 |                                      |
| Schliessen / Close   | 3,5             | 3,5                                  |
| Pressen / Crimp  | 3,5             | 3,5                                  |
| Öffnen / Open  | 5,9             | 5,9                                  |
| Geräuschpegel / Noise level  | 69 dBA          | 69 dBA                               |
| Antrieb / Drive  | 3 kW            | 3 kW**                               |
| Öl / Oil   | 40 l            | 40 l (DC 4 l)                        |
| L x B x H (mm) / L x W x H   | 800 x 530 x 630 | 420 x 535 x 520                      |
| Aggregat (DC) L x B x H /<br>Power Unit (DC) L x W x H                   | -               | 300 x 450 x 560<br>(450 x 270 x 230) |
| Gewicht / Weight   | 140 kg          | 88 kg                                |
| <b>Sonderzubehör / Options</b>   |                 |                                      |
| 12 / 24 Volt   | -               | ✓                                    |
| 1 Phase  | ✓               | 2,2 kW                               |

Paket / Package = Maschine / Machine + PB Ø 17, 20, 24, 28, 32, 40, 44, 50

\* Abhängig von der Armatur / According to the fitting

\*\* Abhängig vom Aggregat / According to the power unit