

SWAGING EQUIPMENT

UNIFLEX EM3 - Ecoline Cutting Machine



Technische Daten / Technical data / Données techniques

	EM 10	EM 3 DC 12V/24V	EM 3 Ecoline	EM 3	EM 2	EM 6 (B)
Werkstatt / Workshop / Atelier SAE R13 & SAE R15*	–	1 1/4"	1"	1 1/4"	1 1/4"	1 1/2"
Produktion / Production / Production SAE R 13 & SAE R 15*	–	3/4"	-	3/4"	3/4"	1"
SAE R12	5/8"	1 1/4"	1 1/4"	1 1/4"	1 1/4"	1 1/2"
Industrie / Industrial / Industrie	1 1/4"	2"	1 1/4"	2"	2"	2"
Max. aussen / Max outside / Maxi extérieur	Ø 45 mm	Ø 80 mm	Ø 52 mm	Ø 80 mm	Ø 80 mm	Ø 65 mm
Geräuschpegel / Noise Level / Bruit	60 dBA	93 dBA	65 dBA	60 dBA	60 dBA	60 dBA
Bremsmotor / Brake Motor / Moteur à frein	–	–	–	✓	✓	✓
Absauganschluß / Suction connection / Conduite d'aspiration	Ø 30 mm	–	Ø 40 mm	Ø 80 mm	Ø 80 mm	Ø 80 mm
Antrieb / Drive / Motorisation	1,1 kW 1~	2,4 / 2,5 kW	2,2 kW	3 kW	3 kW	3 kW
Trennmesser / Cutting blade / Lame de coupe (mm)	160x2,5x20	250x2,5x40	200x1,6x30	275x3x30	275x3x30	300x3x30
Bürsten / Brushing / Dénudeuse à brosse DN 5-6-8-10-12-16-19-25-31-38-51	–	–	–	–	✓	✓ (B)
L-B-H / L-W-H / L-I-H (mm)	360x340x310	470x567x365	400x510x540	540x440x300	630x440x330	780x540x670
Gewicht / Weight / Poids	8 kg	29 kg	20 kg	50 kg	65 kg	73 kg / 88 kg

