

GAUGES

LIQUID FILLED PRESSURE GAUGES - 63MM (2.1/2")

STAINLESS STEEL CASE - LINE MOUNTED - BOTTOM STEM CONNECTION



MILORE REFERENCE PRICE			WORKING PRESSURE	63MM
DUAL SCALE	PG63-			
-1 BAR(30" HG)		40.67	STEADY	3/4 OF FULL SCALE VALUE
-1/+1.5		40.67	FLUCTUATING	2/3 OF FULL SCALE VALUE
-1/+3		40.67	SHORT TIME	FULL SCALE VALUE
-1/+5		40.67		
-1/+9		40.67	MEASURING SYSTEM	COPPER ALLOY BOURDEN
1 BAR/15PSI	PG63-15	40.67	CASE	STAINLESS STEEL
1.6 BAR/20 PSI	PG63-20	40.67	ACCURACY	+ - 1.6% FSD
2 BAR/30 PSI	PG63-30	40.67	CASE DIAMETER	63MM
2.5 BAR/35 PSI	PG63-35	40.67	MODEL NO.	213.53.063
4 BAR/60 PSI	PG63-60	40.67	RANGES	BOTTOM STEM CONNECT
6 BAR/85 PSI	PG63-85	40.67	THREAD	1/4" BSP THREAD
7 BAR/100 PSI	PG63-100	40.67		
10 BAR/145 PSI	PG63-145	40.67		
14 BAR /200 PSI	PG63-200	40.67		
16 BAR/230 PSI	PG63-230	40.67		
20 BAR/300 PSI	PG53-300	40.67		
25 BAR/350 PSI	PG63-350	40.67		
28 BAR/400 PSI	PG63-400	40.67		
40 BAR/580 PSI	PG63-580	40.67		
60 BAR/850 PSI	PG63-850	40.67		
70 BAR/1000 PSI	PG63-1000	40.67		
100BAR/1450 PSI	PG63-1450	40.67		
140BAR/2000PSI	PG63-2000	40.67		
160BAR/2300PSI	PG63-2300	40.67		
200BAR/3000PSI	PG63-3000	40.67		
250BAR/3500PSI	PG63-3500	40.67		
280BAR/4000PSI	PG63-4000	40.67		
400BAR/5800PSI	PG63-5800	40.67		
600BAR/8500PSI	PG63-8500	40.67		
700BAR/10000PSI	PG63-10000	71.85		
1000BAR/14500PSI	PG63-14500	71.85		