


INDUSTRIAL HOSE

T-330 AH




TUBE: BLACK EPDM
REINF.: HIGH TENSILE STEEL CORDS
COVER: RED EPDM - HEAT, ABRASION AND OZONE RESISTANT - PIN PRICKED
APPLIC.: SATURATED STEAM FOR USE IN REFINERIES, SHIPYARDS, CHEMICAL PLANTS AND ALL INDUSTRIAL APPLICATIONS.
S.F.: 10:1
TEMP.: -40°C +208°C (-40°F +406°F)
NORMS: NFT 47263 CAT I TYPE 3 BS 5342/2 CLASS A DIN 2825

SATURATED STEAM 17 BAR (250 WP PSI)

Hose Code	ID mm	ID Inch	OD mm	Wall mm	WP bar	WP PSI	Bend Radius mm	Weight kg/m	Stock Length MT	PRICE
T330AH-013	13	1/2	25	6	17	250	130	0.58	61	22.68
T330AH-016	16	5/8	28	6	17	250	160	0.64	61	39.65
T330AH-019	19	3/4	32	6.5	17	250	190	0.75	61	27.50
T330AH-025	25	1	38	6.5	17	250	250	0.94	61	33.10
T330AH-032	32	1 1/4	46	7	17	250	320	1.39	61	49.34
T330AH-038	38	1 1/2	52	7	17	250	380	1.61	61	55.52
T330AH-051	51	2	67	8	17	250	510	2.24	61	75.74

T-350 AA




TUBE: BLACK EPDM
REINF.: HIGH TENSILE TEXTILE CORDS
COVER: BLACK EPDM - HEAT, ABRASION AND OZONE RESISTANT
APPLIC.: SATURATED STEAM AND HOT WATER DELIVERY IN GENERAL INDUSTRIAL APPLICATIONS.
S.F.: ACCORDING TO BS 5122/A TYPE 2
TEMP.: -40°C +165°C (-40°F +330°F)
NORMS: EXCEEDS BS 5122/A TYPE 2

STEAM 7 BAR (100 WP PSI) / HOT WATER 15 BAR (225 WP PSI)

Hose Code	ID mm	ID Inch	OD mm	Wall mm	WP bar	WP PSI	Bend Radius mm	Weight kg/m	Stock Length MT	PRICE
T350AA-010	10	3/8	20	5	7	100		0.29	61	
T350AA-013	13	1/2	23	5	7	100		0.37	61	16.13
T350AA-016	16	5/8	26	5	7	100		0.43	61	19.48
T350AA-019	19	3/4	31	6	7	100		0.61	61	22.52
T350AA-025	25	1	37	6	7	100		0.76	61	27.29
T350AA-030	30	1 3/16	44	7	7	100		0.91	61	32.68
T350AA-032	32	1 1/4	46	7	7	100		0.95	61	34.04
T350AA-038	38	1 1/2	52	7	7	100		1.11	61	40.70
T350AA-040	40	1 9/16	54	7	7	100		1.16		57.88
T350AA-051	51	2	67	8	7	100		1.70	61	63.53
T350AA-063	63	2 1/2	79	8	7	100		2.08	61	

S-466 OL



TUBE: TRANSPARENT PLASTICIZED PVC - ABRASION AND OZONE RESISTANT
REINF.: WHITE SHOCK RESISTANT RIGID PVC
APPLIC.: LIQUID FOOD AND ALCOHOLIC BEVERAGES (UP TO 28% PROOF) SUCTION AND DELIVERY.
S.F.: 3:1
TEMP.: -5°C +60°C (+23°F +140°F)
NORMS: CEE 90/128 A+B+C

LIQUID FOOD SUCTION & DELIVERY - PVC - STANDARD DUTY

Hose Code	ID mm	ID Inch	OD mm	Wall mm	WP bar	WP PSI	Bend Radius mm	Weight kg/m	Stock Length MT	PRICE
S466OL-020	20	3/4			8	120	90	0.25	50	4.77
S466OL-025	25	1			8	120	113	0.32	50	5.81
S466OL-030	30	1 3/16			7	100	135	0.40	50	5.87
S466OL-032	32	1 1/4			7	100	144	0.42	50	6.86
S466OL-035	35	1 3/8			7	100	158	0.49	50	7.80
S466OL-038	38	1 1/2			6	90	171	0.55	50	8.96
S466OL-040	40	1 9/16			6	90	180	0.58	50	9.43
S466OL-045	45	1 3/4			6	90	203	0.71		11.68
S466OL-051	51	2			5	75	230	0.80	50	13.25
S466OL-055	55	2 1/8			5	75	247	0.86		14.09
S466OL-060	60	2 3/8			5	75	270	0.99	50	16.08
S466OL-063	63	2 1/2			5	75	284	1.04	50	16.97
S466OL-070	70	2 3/4			5	75	315	1.25		20.27
S466OL-076	76	3			5	75	342	1.42	50	23.31
S466OL-080	80	3 1/8			4	60	360	1.56	50	25.30
S466OL-090	90	3 1/2			4	60	405	1.85	50	31.48
S466OL-102	102	4			4	60	459	2.25	50	38.23
S466OL-120	120	4 3/4			3	45	540	2.90		47.19