


# INDUSTRIAL HOSE

## S-470 OO




**TUBE:** TRANSPARENT PLASTICIZED PVC - ABRASION AND OZONE RESISTANT  
**REINF.:** STEEL HELIX WIRE  
**APPLIC.:** GENERAL PURPOSE LIQUID FOOD AND CHEMICALS SUCTION AND DELIVERY - SEE CHEMICAL RESISTANCE CHART  
**S.F.:** 3:1  
**TEMP.:** -5°C +60°C (+23°F +140°F)  
**NORMS:** F.D.A. CEE 90/128 A

## GENERAL PURPOSE FOOD QUALITY - PVC - STEEL HELIX WIRE - STANDARD CONSTRUCTION

Hose Code	ID mm	ID Inch	OD mm	Wall mm	WP bar	WP PSI	Bend Radius mm	Weight kg/m	Stock Length MT	PRICE
S47000-013	13	1/2	19	3	7	100	52	0.21	60	4.66
S47000-014	14	9/16	20	3	6	90	56	0.22	60	6.29
S47000-016	16	5/8	22	3	6	90	64	0.25	60	5.50
S47000-018	18	11/16	26	4	6	90	72	0.32	60	8.59
S47000-020	20	3/4	28	4	5	75	80	0.34	60	7.07
S47000-022	22	7/8	30	4	5	75	88	0.38	60	9.79
S47000-025	25	1	33	4	5	75	100	0.53	60	10.16
S47000-030	30	1 3/16	38	4	4	60	120	0.62	60	15.71
S47000-032	32	1 1/4	40	4	4	60	128	0.66	60	12.78
S47000-035	35	1 3/8	45	5	4	60	140	0.80	60	19.90
S47000-038	38	1 1/2	48	5	4	60	152	0.86	30	16.66
S47000-040	40	1 9/16	50	5	3	45	160	0.90	30	
S47000-045	45	1 3/4	55	5	3	45	180	1.10	30	27.34
S47000-051	51	2	61	5	3	45	204	1.23	30	23.31
S47000-060	60	2 3/8	72	6	2	30	240	1.70	30	35.98
S47000-063	63	2 1/2	75	6	2	30	252	1.78	30	34.41
S47000-076	76	3	90	7	2	30	304	2.45	30	45.52
S47000-080	80	3 1/8	94	7	2	30	320	2.57	30	61.18
S47000-102	102	4	116	7	2	30	408	3.48	30	64.74
S47000-105	105	4 1/8	119	7	2	30	420	3.58		101.30

## T-404 LE




**TUBE:** WHITE CHLOROBUTYL  
**REINF.:** HIGH TENSILE TEXTILE CORDS WITH EMBEDDED STEEL HELIX WIRES  
**COVER:** BLUE EPDM - ABRASION AND OZONE RESISTANT  
**APPLIC.:** LIQUID FOOD, EDIBLE OIL AND ALCOHOLIC BEVERAGES (UP TO 95% PROOF) SUCTION AND DELIVERY. SPECIAL CONSTRUCTION FOR MAXIMUM FLEXIBILITY. STERILIZATION WITH STEAM AT 2.5 BAR 130°C (266°F) MAX 30 MINUTES OR WITH WATER AND MAX 5% SODA.  
**S.F.:** 3:1  
**TEMP.:** -30°C +80°C (-22°F +176°F)  
**NORMS:** F.D.A. ARRETE DU 09/11/94 D.M. 21/03/73

## LIQUID FOOD SUCTION & DELIVERY 10 BAR (150 WP PSI)

Hose Code	ID mm	ID Inch	OD mm	Wall mm	WP bar	WP PSI	Bend Radius mm	Weight kg/m	Stock Length MT	PRICE
T404LE-038	38	1 1/2	50	6	10	150	114	1.27	61	P.O.A
T404LE-051	51	2	63	6	10	150	153	1.68	61	P.O.A
T404LE-063	63	2 1/2	75	6	10	150	189	2.19	61	P.O.A
T404LE-076	76	3	88	6	10	150	228	2.60	61	P.O.A

## T-403 LE



**TUBE:** WHITE CHLOROBUTYL  
**REINF.:** HIGH TENSILE TEXTILE CORDS WITH EMBEDDED STEEL HELIX WIRES  
**COVER:** BLUE EPDM - ABRASION AND OZONE RESISTANT  
**APPLIC.:** LIQUID FOOD, EDIBLE OIL AND ALCOHOLIC BEVERAGES (UP TO 95% PROOF) SUCTION AND DELIVERY. STERILIZATION WITH STEAM AT 2.5 BAR 130°C (266°F) MAX 30 MINUTES OR WITH WATER AND MAX 5% SODA.  
**S.F.:** 3:1  
**TEMP.:** -30°C +80°C (-22°F +176°F)  
**NORMS:** F.D.A. ARRETE DU 09/11/94 D.M. 21/03/73

## LIQUID FOOD SUCTION & DELIVERY 10 BAR (150 WP PSI)

Hose Code	ID mm	ID Inch	OD mm	Wall mm	WP bar	WP PSI	Bend Radius mm	Weight kg/m	Stock Length MT	PRICE
T403LE-019	19	3/4	31	6	10	150	76	0.74		P.O.A
T403LE-025	25	1	37	6	10	150	100	0.90		P.O.A
T403LE-032	32	1 1/4	44	6	10	150	128	1.10		P.O.A
T403LE-038	38	1 1/2	50	6	10	150	152	1.27		P.O.A
T403LE-040	40	1 9/16	52	6	10	150	160	1.32		P.O.A
T403LE-051	51	2	65	7	10	150	204	1.87		P.O.A
T403LE-063	63	2 1/2	77	7	10	150	252	2.47		P.O.A
T403LE-076	76	3	90	7	10	150	304	2.93		P.O.A
T403LE-102	102	4	118	8	10	150	408	3.89		P.O.A