

# INDUSTRIAL HOSE

## T-450 LH




**TUBE:** WHITE CHLOROBUTYL  
**REINF.:** HIGH TENSILE TEXTILE CORDS  
**COVER:** RED EPDM - ABRASION AND OZONE RESISTANT. BLUE COVER ALSO AVAILABLE.  
**APPLIC.:** LIQUID FOOD, EDIBLE OIL AND ALCOHOLIC BEVERAGES (UP TO 95% PROOF) DELIVERY. STERILIZATION WITH STEAM AT 2.5 BAR 130°C (266°F) MAX 30 MINUTES OR WITH WATER AND MAX 5% SODA.  
**S.F.:** 3:1  
**TEMP.:** -30°C +80°C (-22°F +176°F)  
**NORMS:** F.D.A. ARRETE DU 09/11/94 D.M. 21/03/73

## LIQUID FOOD DELIVERY 10 BAR (150 WP PSI)

| Hose Code  | ID mm | ID Inch | OD mm | Wall mm | WP bar | WP PSI | Bend Radius mm | Weight kg/m | Stock Length MT | PRICE |
|------------|-------|---------|-------|---------|--------|--------|----------------|-------------|-----------------|-------|
| T450LH-013 | 13    | 1/2     | 23    | 5       | 10     | 150    |                | 0.38        | 61              | P.O.A |
| T450LH-019 | 19    | 3/4     | 31    | 6       | 10     | 150    |                | 0.62        | 61              | P.O.A |
| T450LH-025 | 25    | 1       | 37    | 6       | 10     | 150    |                | 0.78        | 61              | P.O.A |
| T450LH-032 | 32    | 1 1/4   | 44    | 6       | 10     | 150    |                | 0.95        | 61              | P.O.A |
| T450LH-038 | 38    | 1 1/2   | 50    | 6       | 10     | 150    |                | 1.11        | 61              | P.O.A |
| T450LH-040 | 40    | 1 9/16  | 52    | 6       | 10     | 150    |                | 1.16        | 61              | P.O.A |
| T450LH-051 | 51    | 2       | 65    | 7       | 10     | 150    |                | 1.69        | 61              | P.O.A |
| T450LH-063 | 63    | 2 1/2   | 77    | 7       | 10     | 150    |                | 2.04        |                 | P.O.A |
| T450LH-076 | 76    | 3       | 92    | 8       | 10     | 150    |                | 2.79        | 61              | P.O.A |
| T450LH-102 | 102   | 4       | 118   | 8       | 10     | 150    |                | 3.72        |                 | P.O.A |

## T-741 AA




**TUBE:** BLACK CONDUCTIVE NR - ABRASION RESISTANT  
**REINF.:** HIGH TENSILE STEEL CORDS  
**COVER:** BLACK CONDUCTIVE SBR/NR BLEND - ABRASION AND OZONE RESISTANT  
**APPLIC.:** HIGH PRESSURE CONCRETE PLACEMENT AT CASTING SITE. DESIGNED FOR LONG LASTING SERVICE IN HEAVY DUTY APPLICATIONS.  
**S.F.:** 2.5:1  
**TEMP.:** -30°C +80°C (-22°F +176°F)

## CONCRETE PUMPING 85 BAR (1275 WP PSI) W.P. - EXTRA SERVICE

| Hose Code  | ID mm | ID Inch | OD mm | Wall mm | WP bar | WP PSI | Bend Radius mm | Weight kg/m | Stock Length MT | PRICE |
|------------|-------|---------|-------|---------|--------|--------|----------------|-------------|-----------------|-------|
| T741AA-051 | 51    | 2       | 69    | 9       | 85     | 1275   | 255            | 2.45        | 61              | P.O.A |
| T741AA-063 | 63    | 2 1/2   | 85    | 11      | 85     | 1275   | 325            | 3.90        | 61              | P.O.A |
| T741AA-076 | 76    | 3       | 102   | 13      | 85     | 1275   | 380            | 5.14        | 61              | P.O.A |
| T741AA-102 | 102   | 4       | 130   | 14      | 85     | 1275   | 510            | 7.75        | 61              | P.O.A |
| T741AA-127 | 127   | 5       | 157   | 15      | 85     | 1275   | 635            | 10.51       | 61              | P.O.A |
| T741AA-152 | 152   | 6       | 188   | 18      | 85     | 1275   | 760            | 14.40       |                 | P.O.A |

## T-750 AA



**TUBE:** BLACK CONDUCTIVE NR - ABRASION RESISTANT  
**REINF.:** HIGH TENSILE TEXTILE CORDS  
**COVER:** BLACK CONDUCTIVE SBR/NR BLEND - ABRASION AND OZONE RESISTANT - PIN PRICKED  
**APPLIC.:** SANDBLAST INSTALLATIONS.  
**S.F.:** 3:1  
**TEMP.:** -30°C +80°C (-22°F +176°F)

## SANDBLAST 10 BAR (150 WP PSI)

| Hose Code  | ID mm | ID Inch | OD mm | Wall mm | WP bar | WP PSI | Bend Radius mm | Weight kg/m | Stock Length MT | PRICE |
|------------|-------|---------|-------|---------|--------|--------|----------------|-------------|-----------------|-------|
| T750AA-013 | 13    | 1/2     | 27    | 7       | 10     | 150    |                | 0.52        | 61              |       |
| T750AA-016 | 16    | 5/8     | 30    | 7       | 10     | 150    |                | 0.59        | 61              |       |
| T750AA-019 | 19    | 3/4     | 33    | 7       | 10     | 150    |                | 0.67        | 61              | 19.22 |
| T750AA-025 | 25    | 1       | 40    | 7.5     | 10     | 150    |                | 0.97        | 61              | 23.52 |
| T750AA-032 | 32    | 1 1/4   | 48    | 8       | 10     | 150    |                | 1.18        | 61              | 27.13 |
| T750AA-038 | 38    | 1 1/2   | 55    | 8.5     | 10     | 150    |                | 1.54        | 61              | 37.34 |
| T750AA-040 | 40    | 1 9/16  | 60    | 10      | 10     | 150    |                | 1.80        |                 | 71.07 |
| T750AA-051 | 51    | 2       | 71    | 10      | 10     | 150    |                | 2.21        | 51              | 79.56 |

## T-720 AA



**TUBE:** BLACK CONDUCTIVE NR - ABRASION RESISTANT  
**REINF.:** HIGH TENSILE TEXTILE CORDS WITH EMBEDDED STEEL HELIX WIRES  
**COVER:** BLACK CONDUCTIVE SBR/NR BLEND - ABRASION AND OZONE RESISTANT  
**APPLIC.:** BULK MATERIAL SUCTION AND DELIVERY. DESIGNED FOR DRY CEMENT, GRAINS AND ANIMAL FEED TRANSFER. SPECIAL CONSTRUCTION FOR MAXIMUM FLEXIBILITY.  
**S.F.:** 3:1  
**TEMP.:** -30°C +80°C (-22°F +176°F)

## BULK MATERIAL SUCTION & DELIVERY

| Hose Code  | ID mm | ID Inch | OD mm | Wall mm | WP bar | WP PSI | Bend Radius mm | Weight kg/m | Stock Length MT | PRICE  |
|------------|-------|---------|-------|---------|--------|--------|----------------|-------------|-----------------|--------|
| T720AA-051 | 51    | 2       | 65    | 7       | 10     | 150    | 153            | 1.46        | 61              | 53.74  |
| T720AA-060 | 60    | 2 3/8   | 74    | 7       | 10     | 150    | 180            | 1.88        |                 |        |
| T720AA-063 | 63    | 2 1/2   | 77    | 7       | 10     | 150    | 189            | 1.96        | 61              | 67.88  |
| T720AA-076 | 76    | 3       | 90    | 7       | 10     | 150    | 228            | 2.34        |                 | 100.30 |
| T720AA-102 | 102   | 4       | 116   | 7       | 10     | 150    | 306            | 3.12        |                 | 134.66 |
| T720AA-127 | 127   | 5       | 143   | 8       | 5      | 75     | 508            | 4.75        |                 | 221.50 |
| T720AA-152 | 152   | 6       | 168   | 8       | 5      | 75     | 608            | 5.90        |                 | 267.38 |
| T720AA-203 | 203   | 8       | 221   | 9       | 5      | 75     | 812            | 9.03        |                 | 452.32 |