

INDUSTRIAL HOSE

0BPVC



TUBE: PVC INNER TUBE
REINF.: REINFORCED WITH A 1000 DENIER POLYESTER NYLON BRAID
COVER: 100% FLEXIBLE PVC COVER
APPLIC.: FACTORY AIR SUPPLY - HYDRAULICS
 PNEUMATICS - COOLANT LINES
 CHEMICAL TRANSFER - INSTRUMENTATION
 WATER & FLUID HANDLING - FOOD HANDLING
 BEVERAGE LINES - MATERIALS HANDLING
 COMPRESSED AIR - CROP SPRAYING

PRESSURES.: VALUES STATED ARE BASED ON THE SHORT TERM BURST PRESSURE OF PVC AT 20°C

NOTE: ANY INCREASE IN TEMPERATURE ABOVE 20°C WILL RESULT IN A DECLINE IN BURST PRESSURES

TEMP.: -20°C - +55°C - OCCASIONAL USE UP TO +65°C - COLD BEND TEMPERATURE -45°C


FOOD USE.: THE RAW MATERIALS USED HAVE REGULATORY APPROVAL FOR USE IN FOOD CONTACT APPLICATIONS

CHEMICAL RESISTANCE.: PVC IS RESISTANT TO MOST OXIDISING AND REDUCING AGENTS AND DILUTE ACIDS AND ALKALIS.

CLEAR REINFORCED PVC HOSE

Hose Code	ID mm	ID Inch	OD mm	BP bar	BP PSI	Bend Radius mm	Weight kg/30m	Stock Length MT	PRICE
0BPVC-4	6	1/4"	11	81	1170	76	2.52	30	1.36
0BPVC-5	8	5/16"	13	57	820	102	3.12	30	1.71
0BPVC-6	10	3/8"	15	46	660	114	3.69	30	1.83
0BPVC-8	13	1/2"	18	40	570	140	4.59	30	2.24
0BPVC-10	16	5/8"	22	44	640	180	6.72	30	3.13
0BPVC-12	19	3/4"	25	27	390	203	7.80	30	3.87
0BPVC-16	25	1"	32	32	470	229	11.76	30	5.57
0BPVC-32	32	1 1/4"	41	24	340	267	21.81	30	9.91
0BPVC-38	38	1 1/2"	48	24	340	317	25.35	30	13.41
0BPVC-51	51	2"	62	13	190	406	47.04	30	19.37

0LPVC



TUBE: PVC INNER TUBE
APPLIC.: SLEEVING - SIGHT GLASSES
 LABORATORY USES - DRAIN HOSES
 CHEMICAL DELIVERY - INSTRUMENTATION
 DELIVERY OF FOOD AND BEVERAGES(BEER)

TEMP.: -20°C - +55°C - OCCASIONAL USE UP TO +65°C - COLD BEND TEMPERATURE -45°C

PRESSURES.: FOR PRESSURE APPLICATIONS WE RECOMMEND REINFORCED PVC

UNREINFORCED PVC IS NOT RECOMMENDED FOR PRESSURE APPLICATIONS


FOOD USE.: THE RAW MATERIALS USED HAVE REGULATORY APPROVAL FOR USE IN FOOD CONTACT APPLICATIONS

CHEMICAL RESISTANCE.: PVC IS RESISTANT TO MOST OXIDISING AND REDUCING AGENTS AND DILUTE ACIDS AND ALKALIS.

CLEAR UNREINFORCED PVC HOSE - LIGHT WALL

Hose Code	ID mm	ID Inch	OD mm	Bend Radius mm	Weight kg/30m	Stock Length MT	PRICE
0LPVC-4	6	1/4"	9	72	1.34	30	0.86
0LPVC-5	8	5/16"	11	88	1.68	30	1.11
0LPVC-6	10	3/8"	13	104	2.10	30	1.43
0LPVC-8	13	1/2"	15	120	2.40	30	1.65
0LPVC-10	16	5/8"	19	152	3.10	30	2.15
0LPVC-12	19	3/4"	22	176	3.63	30	2.70

0MPVC



TUBE: PVC INNER TUBE
APPLIC.: SLEEVING - SIGHT GLASSES
 LABORATORY USES - DRAIN HOSES
 CHEMICAL DELIVERY - INSTRUMENTATION
 DELIVERY OF FOOD AND BEVERAGES(BEER)

TEMP.: -20°C - +55°C - OCCASIONAL USE UP TO +65°C - COLD BEND TEMPERATURE -45°C

PRESSURES.: FOR PRESSURE APPLICATIONS WE RECOMMEND REINFORCED PVC

UNREINFORCED PVC IS NOT RECOMMENDED FOR PRESSURE APPLICATIONS

FOOD USE.: THE RAW MATERIALS USED HAVE REGULATORY APPROVAL FOR USE IN FOOD CONTACT APPLICATIONS

CHEMICAL RESISTANCE.: PVC IS RESISTANT TO MOST OXIDISING AND REDUCING AGENTS AND DILUTE ACIDS AND ALKALIS.

CLEAR UNREINFORCED PVC HOSE - MEDIUM WALL

Hose Code	ID mm	ID Inch	OD mm	Bend Radius mm	Weight kg/30m	Stock Length MT	PRICE
0MPVC-4	6	1/4"	12	96	3.20	30	1.67
0MPVC-5	8	5/16"	14	112	3.90	30	2.02
0MPVC-6	10	3/8"	16	120	4.62	30	2.32
0MPVC-8	13	1/2"	19	152	5.67	30	2.87
0MPVC-10	16	5/8"	22	176	6.72	30	3.49
0MPVC-12	19	3/4"	25	200	7.80	30	4.02