

# INDUSTRIAL HOSE

## L-185 AK



**TUBE:** BLACK SYNTHETIC ELASTOMER - OIL MIST RESISTANT  
**REINF.:** HIGH TENSILE TEXTILE CORDS  
**COVER:** YELLOW SYNTHETIC ELASTOMER - ABRASION AND OZONE RESISTANT  
**APPLIC.:** COMPRESSED AIR AND GENERAL INDUSTRIAL APPLICATIONS.  
**S.F.:** 3:1  
**TEMP.:** -10°C +60°C (+14°F +140°F)  
**NORMS:** EXCEEDS DIN 20018/1

## COMPRESSED AIR 20 BAR (300 WP PSI) - STANDARD DUTY

Hose Code	ID mm	ID Inch	OD mm	Wall mm	WP bar	WP PSI	Bend Radius mm	Weight kg/m	Stock Length MT	PRICE
L185AK-013	13	1/2	21	4	20	300	104	0.28	100	4.29
L185AK-019	19	3/4	29	5	20	300	152	0.48	100	6.92
L185AK-025	25	1	36	5.5	20	300	200	0.67	100	9.54

## L-186 AA



**TUBE:** BLACK SYNTHETIC ELASTOMER - OIL MIST RESISTANT  
**REINF.:** HIGH TENSILE TEXTILE CORDS  
**COVER:** BLACK SYNTHETIC ELASTOMER - ABRASION AND OZONE RESISTANT  
**APPLIC.:** COMPRESSED AIR AND GENERAL INDUSTRIAL APPLICATIONS.  
**S.F.:** 3:1  
**TEMP.:** -10°C +60°C (+14°F +140°F)

## COMPRESSED AIR 20 BAR (300 WP PSI) - HEAVY DUTY

Hose Code	ID mm	ID Inch	OD mm	Wall mm	WP bar	WP PSI	Bend Radius mm	Weight kg/m	Stock Length MT	PRICE
L186AA-005	5	3/16	11	2.8	20	300	40	0.09	100	
L186AA-006	6	1/4	14	4	20	300	48	0.17	100	4.99
L186AA-008	8	5/16	17	4.5	20	300	64	0.24	100	6.22
L186AA-010	10	3/8	19	4.5	20	300	80	0.28	100	7.40
L186AA-013	13	1/2	23	5	20	300	104	0.39	100	10.03
L186AA-014	14	9/16	23	4.5	20	300	112	0.34	100	
L186AA-016	16	5/8	26	5	20	300	128	0.42	100	
L186AA-019	19	3/4	30	5.5	20	300	152	0.54	100	13.78
L186AA-025	25	1	37	6	20	300	200	0.73	100	18.71

## T-130 AK




**TUBE:** BLACK SBR/NBR BLEND - OIL MIST RESISTANT  
**REINF.:** HIGH TENSILE STEEL CORDS  
**COVER:** YELLOW SBR - ABRASION AND OZONE RESISTANT - PIN PRICKED  
**APPLIC.:** HIGH PRESSURE COMPRESSED AIR FOR MINE AND QUARRIES DESIGNED FOR LONG LASTING SERVICE AND MAXIMUM SAFETY IN HEAVY DUTY APPLICATIONS. BRAIDED CONSTRUCTION AVAILABLE IN DIAMETERS 38mm AND 51mm.  
**S.F.:** 4:1  
**TEMP.:** -30°C +80°C (-22°F +176°F)

## COMPRESSED AIR - STEEL REINFORCEMENT

Hose Code	ID mm	ID Inch	OD mm	Wall mm	WP bar	WP PSI	Bend Radius mm	Weight kg/m	Stock Length MT	PRICE
T130AK-013	13	1/2	25	6	40	600	65	0.65	30.5	22.79
T130AK-019	19	3/4	31	6	40	600	95	0.81	61	23.70
T130AK-025	25	1	37	6	40	600	125	1.01	30.5/61	28.63
T130AK-032	32	1 1/4	44	6	40	600	160	1.24	61	35.07
T130AK-038	38	1 1/2	52	7	40	600	190	1.66	61	45.47
T130AK-051	51	2	65	7	40	600	255	2.35	61	62.20
T130AK-063	63	2 1/2	83	10	30	450	315	3.60	30.5	91.11
T130AK-076	76	3	96	10	30	450	380	4.29	30.5	108.80
T130AK-102	102	4	122	10	30	450	510	6.21	30.5	157.06

## T-151 AK



**TUBE:** BLACK SBR/NBR BLEND - OIL MIST RESISTANT  
**REINF.:** HIGH TENSILE TEXTILE CORDS  
**COVER:** YELLOW SBR - ABRASION AND OZONE RESISTANT  
**APPLIC.:** COMPRESSED AIR DESIGNED FOR HEAVY DUTY AND MINING APPLICATIONS.  
**S.F.:** 3:1  
**TEMP.:** -30°C +80°C (-22°F +176°F)

## COMPRESSED AIR 20 BAR (300 WP PSI) - HEAVY DUTY

Hose Code	ID mm	ID Inch	OD mm	Wall mm	WP bar	WP PSI	Bend Radius mm	Weight kg/m	Stock Length MT	PRICE
T151AK-013	13	1/2	23	5	20	300		0.43	61	13.25
T151AK-019	19	3/4	31	6	20	300		0.70	61	16.89
T151AK-025	25	1	37	6	20	300		0.86	61	21.13
T151AK-032	32	1 1/4	46	7	20	300		1.28		28.15
T151AK-038	38	1 1/2	52	7	20	300		1.48	61	30.35
T151AK-051	51	2	67	8	20	300		2.21	61	38.72