

INDUSTRIAL HOSE

Gas and Welding

L-076 AE



TUBE: BLACK SBR
REINF.: HIGH TENSILE TEXTILE CORDS
COVER: BLUE SBR/EPDM BLEND - ABRASION AND OZONE RESISTANT
APPLIC.: OXYGEN WELDING.
S.F.: 3:1
TEMP.: -25°C +80°C (-13°F +176°F)
NORMS: EN 559 AS 1335

WELDING 20 BAR (300 WP PSI) - EN 559 - AS 1335

| Hose Code | ID mm | ID Inch | OD mm | Wall mm | WP bar | WP PSI | Bend Radius mm | Weight kg/m | Stock Length MT | PRICE |
|------------|-------|---------|-------|---------|--------|--------|----------------|-------------|-----------------|-------|
| L076AE-005 | 5 | 3/16 | 12 | 3.5 | 20 | 300 | 40 | 0.14 | 100 | |
| L076AE-006 | 6 | 1/4 | 13 | 3.5 | 20 | 300 | 48 | 0.16 | 100 | 3.09 |
| L076AE-008 | 8 | 5/16 | 15 | 3.5 | 20 | 300 | 64 | 0.19 | 100 | 3.25 |
| L076AE-010 | 10 | 3/8 | 17 | 3.5 | 20 | 300 | 80 | 0.22 | 100 | 3.82 |

L-076 AH



TUBE: BLACK SBR
REINF.: HIGH TENSILE TEXTILE CORDS
COVER: RED SBR/EPDM BLEND - ABRASION AND OZONE RESISTANT
APPLIC.: ACETYLENE WELDING.
S.F.: 3:1
TEMP.: -25°C +80°C (-13°F +176°F)
NORMS: EN 559 AS 1335

WELDING 20 BAR (300 WP PSI) - EN 559 - AS 1335

| Hose Code | ID mm | ID Inch | OD mm | Wall mm | WP bar | WP PSI | Bend Radius mm | Weight kg/m | Stock Length MT | PRICE |
|------------|-------|---------|-------|---------|--------|--------|----------------|-------------|-----------------|-------|
| L076AH-005 | 5 | 3/16 | 12 | 3.5 | 20 | 300 | 40 | 0.14 | 100 | |
| L076AH-006 | 6 | 1/4 | 13 | 3.5 | 20 | 300 | 48 | 0.16 | 100 | 3.09 |
| L076AH-008 | 8 | 5/16 | 15 | 3.5 | 20 | 300 | 64 | 0.19 | 100 | 3.25 |
| L076AH-010 | 10 | 3/8 | 17 | 3.5 | 20 | 300 | 80 | 0.22 | 100 | 3.82 |

L-076 EH



TUBE: BLACK SBR
REINF.: HIGH TENSILE TEXTILE CORDS
COVER: RED,BLUE SBR/EPDM BLEND - ABRASION AND OZONE RESISTANT
APPLIC.: OXYGEN/ACETYLENE TWIN WELDING.
S.F.: 3:1
TEMP.: -25°C +80°C (-13°F +176°F)
NORMS: EN 559 AS 1335

TWIN WELDING 20 BAR (300 WP PSI) - OXYGEN/ACETYLENE - EN 559

| Hose Code | ID mm | ID Inch | OD mm | Wall mm | WP bar | WP PSI | Bend Radius mm | Weight kg/m | Stock Length MT | PRICE |
|------------|-------|---------|-------|---------|--------|--------|----------------|-------------|-----------------|-------|
| L076EH-005 | 5+5 | 3/16 | 12 | 3.5 | 20 | 300 | 40 | 0.28 | 100 | |
| L076EH-006 | 6+6 | 1/4 | 13 | 3.5 | 20 | 300 | 48 | 0.32 | 100 | 7.70 |
| L076EH-008 | 8+8 | 5/16 | 15 | 3.5 | 20 | 300 | 64 | 0.38 | 100 | 8.43 |
| L076EH-010 | 10+10 | 3/8 | 17 | 3.5 | 20 | 300 | 80 | 0.44 | 100 | 9.85 |

L-088 AI



TUBE: BLACK SYNTHETIC ELASTOMER
REINF.: HIGH TENSILE TEXTILE CORDS
COVER: ORANGE SYNTHETIC ELASTOMER - ABRASION AND OZONE RESISTANT
APPLIC.: LPG AND NATURAL GAS.
S.F.: 3:1
TEMP.: -10°C +60°C (+14°F +140°F)
NORMS: BS 3212/2 NEN 5654*

LPG - NATURAL GAS 25 BAR (375 WP PSI) - BS 3212/2 - NEN 5654

| Hose Code | ID mm | ID Inch | OD mm | Wall mm | WP bar | WP PSI | Bend Radius mm | Weight kg/m | Stock Length MT | PRICE |
|------------|-------|---------|-------|---------|--------|--------|----------------|-------------|-----------------|-------|
| L088AI-006 | 6 | 1/4 | 13 | 3.5 | 25 | 375 | 48 | 0.14 | 100 | 2.99 |
| L088AI-008 | 8 | 5/16 | 15 | 3.5 | 25 | 375 | 64 | 0.17 | 100 | 3.35 |
| L088AI-010 | 10 | 3/8 | 17 | 3.5 | 25 | 375 | 80 | 0.20 | 100 | 4.14 |