

INDUSTRIAL HOSE

L-680 AA



TUBE: BLACK SYNTHETIC ELASTOMER
REINF.: HIGH TENSILE TEXTILE CORDS -
 ANTISTATIC WIRE DIA. 13 mm AND ABOVE
COVER: BLACK SYNTHETIC ELASTOMER - ABRASION,
 OZONE AND HYDROCARBON RESISTANT
APPLIC.: LOW PRESSURE OR GRAVITY FUEL AND OIL
 TRANSFER.
S.F.: 3:1
TEMP.: -10°C +60°C (+14°F +140°F)

FUEL AND OIL DELIVERY 10 BAR (150 WP PSI)

Hose Code	ID mm	ID Inch	OD mm	Wall mm	WP bar	WP PSI	Bend Radius mm	Weight kg/m	Stock Length MT	PRICE
L680AA-006	6	1/4	13	3.5	10	150	48	0.14	100	3.72
L680AA-008	8	5/16	15	3.5	10	150	64	0.17	100	4.24
L680AA-010	10	3/8	17	3.5	10	150	80	0.20	100	4.98
L680AA-013	13	1/2	20	3.5	10	150	104	0.24	100	6.08
L680AA-019	19	3/4	27	4	10	150	152	0.39	100	9.32
L680AA-025	25	1	35	5	10	150	200	0.61	100	14.93

T-352 AA



TUBE: BLACK EPDM
REINF.: HIGH TENSILE TEXTILE CORDS
COVER: BLACK EPDM - HEAT, ABRASION AND
 OZONE RESISTANT
APPLIC.: RADIATOR HOSE.
S.F.: 3:1
TEMP.: -40°C +120°C (-40°F +248°F)
NORMS: EXCEEDS DIN 73411

RADIATOR 5 BAR (75 WP PSI) - DIN 73411

Hose Code	ID mm	ID Inch	OD mm	Wall mm	WP bar	WP PSI	Bend Radius mm	Weight kg/m	Stock Length MT	PRICE
T352AA-013	13	1/2	21	4	5	75		0.29	1	11.47
T352AA-016	16	5/8	24	4	5	75		0.33	1	12.47
T352AA-018	18	11/16	26	4	5	75		0.36	1	12.94
T352AA-019	20	3/4	28	4	5	75		0.39	1	13.72
T352AA-022	22	7/8	30	4	5	75		0.42	1	14.30
T352AA-025	25	1	33	4	5	75		0.47	1	15.66
T352AA-028	28	1 1/8	36	4	5	75		0.52	1	16.76
T352AA-030	30	1 3/16	38	4	5	75		0.55	1	17.39
T352AA-032	32	1 1/4	40	4	5	75		0.58	1	18.28
T352AA-035	35	1 3/8	43	4	5	75		0.62	1	19.07
T352AA-038	38	1 1/2	48	5	5	75		0.86	1	24.83
T352AA-040	40	1 9/16	50	5	5	75		0.89	1	25.72
T352AA-042	42	1 5/8	52	5	5	75		0.93	1	26.82
T352AA-045	45	1 3/4	55	5	5	75		0.99	1	28.49
T352AA-048	48	1 7/8	58	5	5	75		1.05	1	30.22
T352AA-051	51	2	61	5	5	75		1.12	1	32.42
T352AA-055	55	2 1/8	65	5	5	75		1.19	1	33.21
T352AA-057	57	2 1/4	67	5	5	75		1.23	1	34.36
T352AA-060	60	2 3/8	70	5	5	75		1.29	1	36.09
T352AA-063	63	2 1/2	73	5	5	75		1.35	1	37.82
T352AA-070	70	2 3/4	80	5	5	75		1.45	1	39.33
T352AA-076	76	3	86	5	5	75		1.56	1	42.42
T352AA-080	80	3 1/8	90	5	5	75		1.65	1	44.83
T352AA-090	90	3 1/2	102	6	5	75		2.02	1	54.89
T352AA-102	102	4	114	6	5	75		2.27	1	61.75
T352AA-110	110	4 5/16	122	6	5	75		2.42	1	120.88

L-375 AA



TUBE: BLACK EPDM
REINF.: HIGH TENSILE TEXTILE CORDS
COVER: BLACK EPDM - ABRASION AND
 OZONE RESISTANT
APPLIC.: HOT WATER AND GENERAL INDUSTRIAL
 APPLICATIONS. ALSO SUITABLE FOR
 BASED LIQUIDS IN CAR HEATERS.
S.F.: 3:1
TEMP.: -35°C +100°C (-31°F +212°F)

HOT WATER 10 BAR (150 WP PSI)

Hose Code	ID mm	ID Inch	OD mm	Wall mm	WP bar	WP PSI	Bend Radius mm	Weight kg/m	Stock Length MT	PRICE
L375AA-013	13	1/2	19	3	10	150	130	0.24	100	6.18
L375AA-016	16	5/8	22	3	10	150	160	0.28	100	7.07
L375AA-019	19	3/4	27	4	10	150	190	0.45	100	10.32
L375AA-025	25	1	33	4	10	150	250	0.57	100	13.88