

INDUSTRIAL HOSE

T-650 AA



TUBE: BLACK CONDUCTIVE NBR
REINF.: HIGH TENSILE TEXTILE CORDS
COVER: BLACK CONDUCTIVE NBR/PVC BLEND - ABRASION, OZONE AND HYDROCARBON RESISTANT
APPLIC.: FUEL AND OIL DELIVERY WITH UP TO 50% AROMATIC CONTENT.
S.F.: 3:1
TEMP.: -30°C +80°C (-22°F +176°F)

FUEL AND OIL DELIVERY 10 BAR (150 WP PSI)

Hose Code	ID mm	ID Inch	OD mm	Wall mm	WP bar	WP PSI	Bend Radius mm	Weight kg/m	Stock Length MT	PRICE
T650AA-013	13	1/2	23	5	10	150		0.35		19.59
T650AA-016	16	5/8	26	5	10	150		0.41		21.89
T650AA-019	19	3/4	29	5	10	150		0.46		
T650AA-025	25	1	35	5	10	150		0.58	61	25.14
T650AA-032	32	1 1/4	42	5	10	150		0.71	61	44.15
T650AA-038	38	1 1/2	48	5	10	150		0.83	61	50.18
T650AA-051	51	2	61	5	10	150		1.10		65.05
T650AA-076	76	3	88	6	10	150		1.95		103.91
T650AA-102	102	4	114	6	10	150		2.64		140.53
T650AA-127	127	5	141	7	10	150		3.26		
T650AA-152	152	6	166	7	10	150		3.98		

T-658 AA



TUBE: BLACK CONDUCTIVE NBR
REINF.: BRAIDED HIGH TENSILE TEXTILE CORDS
COVER: BLACK CONDUCTIVE NBR/PVC BLEND - ABRASION, OZONE AND HYDROCARBON RESISTANT
APPLIC.: FUEL AND OIL DELIVERY WITH UP TO 50% AROMATIC CONTENT. DESIGNED FOR REELING APPLICATIONS. ALSO SUITABLE FOR TANK CLEANING APPLICATIONS.
S.F.: 3:1
TEMP.: -30°C +70°C (-22°F +158°F)
NORMS: EN 1360

DOMESTIC FUEL / REELING 16 BAR (240 WP PSI) - EN 1360

Hose Code	ID mm	ID Inch	OD mm	Wall mm	WP bar	WP PSI	Bend Radius mm	Weight kg/m	Stock Length MT	PRICE
T658AA-025	25	1	37	6	16	240	125	0.79		69.77
T658AA-032	32	1 1/4	44	6	16	240	160	0.95	61	52.53
T658AA-035	35	1 3/8	47	6	16	240	175	1.01		54.42
T658AA-038	38	1 1/2	51	6.5	16	240	190	1.11		57.61
T658AA-040	40	1 9/16	53	6.5	16	240	200	1.15		62.59
T658AA-051	51	2	67	8	16	240	255	1.63		83.54

T-154 AA



TUBE: BLACK SBR/NBR BLEND - OIL MIST RESISTANT
REINF.: HIGH TENSILE TEXTILE CORDS
COVER: BLACK SBR - ABRASION AND OZONE RESISTANT
APPLIC.: GENERAL PURPOSE WATER DISCHARGE.
S.F.: 3:1
TEMP.: -30°C +80°C (-22°F +176°F)

WATER DELIVERY 10 BAR (150 WP PSI)

Hose Code	ID mm	ID Inch	OD mm	Wall mm	WP bar	WP PSI	Bend Radius mm	Weight kg/m	Stock Length MT	PRICE
T154AA-019	19	3/4	27	4	10	150		0.42		P.O.A
T154AA-025	25	1	33	4	10	150		0.53		P.O.A
T154AA-030	30	1 3/16	40	5	10	150		0.78		P.O.A
T154AA-032	32	1 1/4	42	5	10	150		0.82	61	P.O.A
T154AA-035	35	1 3/8	45	5	10	150		0.90		P.O.A
T154AA-038	38	1 1/2	48	5	10	150		0.96	61	P.O.A
T154AA-040	40	1 9/16	50	5	10	150		1.01	61	P.O.A
T154AA-045	45	1 3/4	55	5	10	150		1.12	61	P.O.A
T154AA-051	51	2	61	5	10	150		1.27	61	P.O.A
T154AA-060	60	2 3/8	72	6	10	150		1.81	61	P.O.A
T154AA-063	63	2 1/2	75	6	10	150		1.89	61	P.O.A
T154AA-076	76	3	88	6	10	150		2.27	61	P.O.A
T154AA-090	90	3 1/2	102	6	10	150		2.66		P.O.A
T154AA-102	102	4	114	6	10	150		3.06	61	P.O.A
T154AA-115	115	4 1/2	127	6	10	150		3.40	61	P.O.A
T154AA-127	127	5	141	7	10	150		3.78	30.5	P.O.A
T154AA-152	152	6	166	7	10	150		4.59	30.5	P.O.A
T154AA-203	203	8	219	8	10	150		6.82	30.5	P.O.A