

INDUSTRIAL HOSE

P-286 EE




TUBE: BLUE PLASTICIZED PVC
REINF.: HIGH TENSILE TEXTILE CORDS
COVER: BLUE PLASTICIZED PVC - ABRASION AND OZONE RESISTANT
APPLIC.: LAY FLAT WATER DISCHARGE FOR GENERAL INDUSTRIAL APPLICATION.
S.F.: 3:1
TEMP.: -10°C +60°C (+14°F +140°F)

LAY FLAT WATER DISCHARGE - PVC - STANDARD DUTY

Hose Code	ID mm	ID Inch	OD mm	Wall mm	WP bar	WP PSI	Bend Radius mm	Weight kg/m	Stock Length MT	PRICE
P286EE-038	38	1 1/2			5	75		0.22	100	3.88
P286EE-051	51	2			5	75		0.28	100	4.98
P286EE-063	63	2 1/2			4	60		0.36	100	6.29
P286EE-076	76	3			4	60		0.45	100	7.91
P286EE-102	102	4			4	60		0.65	100	11.31
P286EE-127	127	5			3	45		1.00	50	22.78
P286EE-152	152	6			3	45		1.30	50	22.78
P286EE-203	203	8			3	45		2.00	50	34.78

T-202 AA



TUBE: BLACK EPDM
REINF.: HIGH TENSILE TEXTILE CORDS WITH EMBEDDED STEEL HELIX WIRES
COVER: BLACK EPDM - ABRASION AND OZONE RESISTANT
APPLIC.: LIQUID SUCTION AND DELIVERY IN IRRIGATION, DEWATERING AND GENERAL INDUSTRIAL APPLICATIONS. GOOD RESISTANCE TO AGRICULTURAL CHEMICALS - SEE CHEMICAL RESISTANCE CHART.
S.F.: 3:1
TEMP.: -30°C +80°C (-22°F +176°F)

GENERAL PURPOSE SUCTION & DELIVERY 10 BAR (150 PSI) - EPDM

Hose Code	ID mm	ID Inch	OD mm	Wall mm	WP bar	WP PSI	Bend Radius mm	Weight kg/m	Stock Length MT	PRICE
T202AA-025	25	1	35	5	10	150	100	0.69	61	20.27
T202AA-030	30	1 3/16	40	5	10	150	120	0.79		
T202AA-032	32	1 1/4	42	5	10	150	128	0.84	61	23.31
T202AA-035	35	1 3/8	45	5	10	150	140	0.90		
T202AA-038	38	1 1/2	48	5	10	150	152	0.96	61	25.77
T202AA-040	40	1 9/16	50	5	10	150	160	1.01	61	
T202AA-045	45	1 3/4	55	5	10	150	180	1.12	61	
T202AA-051	51	2	61	5	10	150	204	1.25	61	30.54
T202AA-055	55	2 1/8	65	5	10	150	220	1.34		
T202AA-057	57	2 1/4	67	5	10	150	220	1.38		
T202AA-060	60	2 3/8	72	6	10	150	240	1.75	61	
T202AA-063	63	2 1/2	75	6	10	150	252	1.83	61	46.09
T202AA-070	70	2 3/4	82	6	10	150	280	2.03		
T202AA-076	76	3	88	6	10	150	304	2.18	61	48.03
T202AA-080	80	3 1/8	92	6	10	150	320	2.36	61	50.39
T202AA-090	90	3 1/2	102	6	10	150	360	2.61	61	61.65
T202AA-102	102	4	114	6	10	150	408	2.92	61	55.52
T202AA-110	110	4 5/16	122	6	10	150	440	3.13		
T202AA-115	115	4 1/2	127	6	10	150	460	3.26	30.5	
T202AA-120	120	4 3/4	134	7	10	150	600	4.40	20	
T202AA-127	127	5	141	7	10	150	635	4.63	30.5	109.26
T202AA-133	133	5 1/4	147	7	10	150	665	4.83		
T202AA-152	152	6	166	7	10	150	760	5.80	30.5/61	119.05
T202AA-160	160	6 5/16	174	7	10	150	800	6.08		
T202AA-203	203	8	221	9	10	150	1015	9.83	6.1	233.18
T202AA-254	254	10	272	9	10	150	1270	13.45	6.1	
T202AA-300	300	12	320	10	10	150	1525	18.18		

S-267 BE



TUB.: BLUE SHOCK RESISTANT RIGID PVC
REINF.: BLUE SHOCK RESISTANT RIGID PVC
APPLIC.: HEAVY DUTY LIQUID SUCTION IN SLUDGE TANKERS, DEWATERING AND GENERAL INDUSTRIAL APPLICATIONS. GOOD LOW TEMPERATURE AND RESISTANCE TO AGRICULTURAL CHEMICALS - SEE CHEMICAL RESISTANCE CHART.
S.F.: 3:1
TEMP.: -20°C +60°C (-4°F +140°F)

WATER SUCTION & DELIVERY - PVC - MEDIUM DUTY - SUPER ELASTIC

Hose Code	ID mm	ID Inch	OD mm	Wall mm	WP bar	WP PSI	Bend Radius mm	Weight kg/m	Stock Length MT	PRICE
S267BE-025	25	1			7	100	100	0.41	50	7.07
S267BE-032	32	1 1/4			7	100	128	0.60	50	9.01
S267BE-038	38	1 1/2			7	100	152	0.70	50	10.48
S267BE-051	51	2			5	75	204	1.00	50	14.98
S267BE-060	60	2 3/8			5	75	240	1.28	50	26.14
S267BE-063	63	2 1/2			5	75	252	1.34	50	19.69
S267BE-076	76	3			5	75	304	1.75	50	25.72
S267BE-080	80	3 1/8			5	75	320	1.84	30	37.55
S267BE-090	90	3 1/2			4	60	360	2.26	30	46.09
S267BE-102	102	4			4	60	408	2.70	30	39.65
S267BE-110	110	4 5/16			4	60	440	3.10	20	63.17
S267BE-120	120	4 3/4			4	60	480	3.60	20	73.22
S267BE-127	127	5			4	60	508	3.80	20	57.30
S267BE-152	152	6			3	45	608	4.85	20	73.12
S267BE-203	203	8			3	45	812	9.10	10	148.17