

INDUSTRIAL HOSE

S-264 GL




TUBE: GREEN TRANSPARENT PLASTICIZED PVC - ABRASION AND OZONE RESISTANT
REINF.: WHITE SHOCK RESISTANT RIGID PVC
APPLIC.: LIQUID SUCTION AND DELIVERY.
TEMP.: -5°C +60°C (+23°F +140°F)

WATER SUCTION & DELIVERY - PVC - LIGHT DUTY

Hose Code	ID mm	ID Inch	OD mm	Wall mm	WP bar	WP PSI	Bend Radius mm	Weight kg/m	Stock Length MT	PRICE
S264GL-020	20	3/4			7	100	110	0.22	50	3.60
S264GL-025	25	1			7	100	138	0.28	50	4.29
S264GL-032	32	1 1/4			6	90	176	0.37	50	5.25
S264GL-038	38	1 1/2			5	75	209	0.49	50	6.84
S264GL-051	51	2			5	75	281	0.72	50	10.02

S-266 LL




TUBE: WHITE THERMOPLASTIC ELASTOMER
REINF.: WHITE SHOCK RESISTANT RIGID PVC
APPLIC.: SANITARY HOSE FOR MARINE APPLICATIONS.
S.F.: 3:1
TEMP.: -5°C +60°C (+23°F +140°C)

MARINE SANITARY HOSE - PVC

Hose Code	ID mm	ID Inch	OD mm	Wall mm	WP bar	WP PSI	Bend Radius mm	Weight kg/m	Stock Length MT	PRICE
S266LL-019	19	3/4			8	120	75	0.30	30	6.57
S266LL-025	25	1			8	120	120	0.38	30	8.16
S266LL-038	38	1 1/2			6	90	170	0.58	30	11.02

S-668 EL




TUBE: BLUE PLASTICIZED PVC - ABRASION, OZONE AND HYDROCARBON RESISTANT
REINF.: WHITE SHOCK RESISTANT RIGID PVC
APPLIC.: FUEL AND OIL SUCTION AND DELIVERY.
S.F.: 3:1
TEMP.: -10°C +60°C (+14°F +140°F)

FUEL AND OIL SUCTION & DELIVERY - PVC - HEAVY CONSTRUCTION

Hose Code	ID mm	ID Inch	OD mm	Wall mm	WP bar	WP PSI	Bend Radius mm	Weight kg/m	Stock Length MT	PRICE
S668EL-025	25	1			7	100	150	0.52	50	12.35
S668EL-032	32	1 1/4			6	90	192	0.65	50	15.90
S668EL-038	38	1 1/2			6	90	228	0.76	50	17.91
S668EL-040	40	1 9/16			7	100	240	0.80	40	18.92
S668EL-051	51	2			5	75	306	1.15	50	28.20
S668EL-060	60	2 3/8			4	60	360	1.47	40	36.52
S668EL-063	63	2 1/2			4	60	378	1.54	50	37.63
S668EL-076	76	3			4	60	456	2.00	50	47.06
S668EL-080	80	3 1/8			4	60	480	2.10	30	49.34
S668EL-090	90	3 1/2			4	60	540	2.85	30	
S668EL-102	102	4			3	45	612	3.20	20	75.21

T-350 LL



TUBE: WHITE EPDM
REINF.: HIGH TENSILE TEXTILE CORDS
COVER: WHITE EPDM - HEAT, ABRASION AND OZONE RESISTANT
APPLIC.: LIQUID FOOD, SATURATED STEAM AND HOT WATER DELIVERY IN GENERAL INDUSTRIAL APPLICATIONS. SPECIALLY DESIGNED FOR WASH DOWN USE IN THE FOOD AND DAIRY INDUSTRIES.
S.F.: ACCORDING TO BS 5122/A TYPE 2
TEMP.: -40°C +165°C (-40°F +330°F)
NORMS: EXCEEDS BS 5122/A TYPE 2. FDA

STEAM 7 BAR (100 WP PSI) / HOT WATER 15 BAR (225 WP PSI)

Hose Code	ID mm	ID Inch	OD mm	Wall mm	WP bar	WP PSI	Bend Radius mm	Weight kg/m	Stock Length MT	PRICE
T350LL-013	13	1/2	23	5	7	100		0.39	61	17.01
T350LL-019	19	3/4	31	6	7	100		0.64	61	24.27
T350LL-025	25	1	37	6	7	100		0.79	61	29.36
T350LL-032	32	1 1/4	46	7	7	100		1.19		