

SWAGE FITTINGS

3000 P.S.I. SOLID FLANGE

3000 P.S.I. SOLID FLANGE

MILORE REFERENCE

SIZE	O.D. -INS.	O.D. -MMS	BORE	A260	A262	A264
				STRAIGHT	45 DEG	90 DEG
-8	1.18"	30.0	1/2"	17.72	28.31	28.31
-12-8	1.50"	38.1	1/2"	23.31	35.74	35.74
-12-10	1.50"	38.1	5/8"	28.17	31.80	39.71
-12	1.50"	38.1	3/4"	20.65	33.76	35.81
-16-12	1.75"	44.5	3/4"	26.65	41.03	41.03
-16	1.75"	44.5	1"	24.40	41.03	48.02
-20-16	2"	50.8	1"	42.10	60.71	61.00
-20	2"	50.8	1.1/4"	37.22	65.69	78.88
-24-20	2.37"	60.2	1.1/4"	120.44	103.23	124.66
-24	2.37"	60.2	1.1/2"	114.30	111.42	120.04
-32-24	2.13/16"	71.4	1.1/2"	84.47	192.65	192.59
-32	2.13/16"	71.4	2"	93.38	217.50	217.50

6000 P.S.I. SOLID FLANGE

6000 P.S.I. SOLID FLANGE

MILORE REFERENCE

SIZE	O.D. -INS.	O.D. -MMS	BORE	A270	A272	A274
				STRAIGHT	45 DEG	90 DEG
-8	1.25"	31.7	1/2"	21.96	29.82	33.15
-12-8	1.62"	41.2	1/2"	24.27	57.83	57.83
-12-10	1.62"	41.2	5/8"	21.95	33.21	34.85
-12	1.62"	41.2	3/4"	23.47	37.55	39.66
-16-12	1.87"	47.6	3/4"	35.81	46.23	53.74
-16	1.87"	47.6	1"	34.37	51.93	53.74
-20-16	2.12"	53.5	1"	47.39	73.57	74.33
-20	2.12"	53.5	1.1/4"	47.85	79.31	105.05
-24-20	2.50"	63.5	1.1/4"	71.31	120.88	131.40
-24	2.50"	63.5	1.1/2"	75.62	132.30	173.50
-32-24	3.12"	79.4	1.1/2"	124.43	344.60	338.31
-32	3.12"	79.4	2"	131.24	344.60	278.67

FLANGE O' RINGS AND FLAT SEALS ARE NOW AVAILABLE